

传感器/MEMS

霍尔IC 	P.80	地磁传感器IC 	P.81
电流传感器IC 	P.81	照度传感器IC 	P.81
颜色传感器IC 	P.81	气压传感器IC 	P.82
温度传感器IC 	P.82	震动传感器用放大器 	P.82
加速度传感器 	P.82		

 点击图标即可链接至罗姆官网的产品介绍页面。可通过官网确认最新情况。

霍尔IC

两极检测霍尔IC 检测出S极和N极时，输出ON(低电平有效)

Part No.	Supply Voltage (V)	Operate Point (mT)		Pulse Drive Period (ms)	Supply Current (Avg.) (μA)	Output	Operating Temperature (°C)	Package
		S-pole	N-pole					
BD7411G	4.5 to 5.5	+3.4	-3.4	—	2.0 (mA)	CMOS	-40 to +85	SSOP5

两极检测(极性判别输出) 霍尔IC 具有S极和N极检测用2个输出，能够辨别极性

Part No.	Supply Voltage (V)	Operate Point (mT)		Pulse Drive Period (ms)	Supply Current (Avg.) (μA)	Output	Operating Temperature (°C)	Package (mm)
		S-pole	N-pole					
BU52272NUZ	1.65 to 3.60	+2.4	-2.4	50	4.4	CMOS (2 Outputs: S, N pole)	-40 to +85	VSON04Z1114A 1.1x1.4, H=Max 0.4
BU52072GWZ	1.65 to 3.60	+2.4	-2.4	50	4.4	CMOS (2 Outputs: S, N pole)	-40 to +85	UCSP35L1 0.8x0.8, H=Max 0.4
BU52073GWZ	1.65 to 3.60	+4.1	-4.1	50	4.4	CMOS (2 Outputs: S, N pole)	-40 to +85	UCSP35L1 0.8x0.8, H=Max 0.4
BU52074GWZ	1.65 to 3.60	+6.3	-6.3	50	4.4	CMOS (2 Outputs: S, N pole)	-40 to +85	UCSP35L1 0.8x0.8, H=Max 0.4
BU52075GWZ	1.65 to 3.60	+9.5	-9.5	50	5.0	CMOS (2 Outputs: S, N pole)	-40 to +85	UCSP35L1 0.8x0.8, H=Max 0.4
BU52737GWZ	2.5 to 4.5	+15.0	+15.0	50	0.8	CMOS (2 Outputs: S, N pole)	-40 to +85	UCSP35L1 0.8x0.8, H=Max 0.4
BU52077GWZ	1.65 to 3.60	+15.0	-15.0	50	5.0	CMOS (2 Outputs: S, N pole)	-40 to +85	UCSP35L1 0.8x0.8, H=Max 0.4
BU52078GWZ	1.65 to 3.60	+24.0	-24.0	50	5.0	CMOS (2 Outputs: S, N pole)	-40 to +85	UCSP35L1 0.8x0.8, H=Max 0.4

工业设备用 交变检测霍尔IC

Part No.	Supply Voltage (V)	Operate Point (mT)		Magnetic Signal Input Frequency (Hz)	Supply Current (μA)	Output	Operating Temperature (°C)	Package (mm)
		S-pole	N-pole					
New BD54132G-LBZ	2.5 to 38	2.7	-2.7	20k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12

车载用 单极检测霍尔IC

Part No.	Supply Voltage (V)	Operate Point (mT)		Magnetic Signal Input Frequency (Hz)	Supply Current (μA)	Output	Operating Temperature (°C)	Package (mm)	Automotive Grade AEC-Q100
		S-pole	N-pole						
BD53103G-CZ	2.7 to 38	3.5	—	10k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12	YES
BD53104G-CZ	2.7 to 38	7.5	—	10k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12	YES
BD53105G-CZ	2.7 to 38	10.0	—	10k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12	YES
BD53106G-CZ	2.7 to 38	12.5	—	10k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12	YES
BD53107G-CZ	2.7 to 38	18.0	—	10k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12	YES
BD53108G-CZ	2.7 to 38	28.0	—	10k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12	YES

车载用 交变检测霍尔IC

Part No.	Supply Voltage (V)	Operate/Release Point (mT)		Magnetic Signal Input Frequency (Hz)	Supply Current (μA)	Output	Operating Temperature (°C)	Package (mm)	Automotive Grade AEC-Q100
		Bop	Brp						
BD54102G-CZ	2.7 to 38	2.0	-2.0	10k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12	YES
BD54103G-CZ	2.7 to 38	5.0	-5.0	10k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12	YES
BD54104G-CZ	2.7 to 38	7.5	-7.5	10k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12	YES
BD54105G-CZ	2.7 to 38	10.0	-10.0	10k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12	YES
BD54107G-CZ	2.7 to 38	15.0	-15.0	10k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12	YES

地磁传感器IC

三轴数字地磁传感器IC

Part No.	Supply Voltage (V)	Magnetic Measurement (μ T)	Magnetic Sensitivity (μ T/LSB)	Current Consumption (μ A)	I/F	Operating Temperature (°C)	Package (mm)
BM1423GMV	1.7 to 3.6	$\pm 1,200$	0.042	150	I ² C	-40 to +85	MLGA010V020A 2.0x2.0, H=Max 1.0

电流传感器IC

非接触式电流传感器IC

Part No.	Supply Voltage (V)	Magnetic Measurement (μ T)	Magnetic Sensitivity (μ T/LSB)	Current Consumption (μ A)	I/F	Operating Temperature (°C)	Package (mm)
BM14270AMUV-LB	2.7 to 5.5	± 280	0.045	70	I ² C	-40 to +125	VQFN20QV3535 3.5x3.5, H=Max 1.0

电流检测放大器IC

Part No.	Ch	Supply Voltage (V)	Quiescent Current (μ A)	Common Mode Voltage (V)	Gain (V/V)	Gain Accuracy (%)	Operating Temperature (°C)	Package (mm)
BD14210G-LA	1	2.7 to 5.5	170	-0.2 to +26	20	± 1 (Max)	-40 to +125	SSOP6 2.9x2.8, H=Max 1.25
New BD14211G-LA	1	2.7 to 5.5	170	-0.2 to +26	50	± 1 (Max)	-40 to +125	SSOP6 2.9x2.8, H=Max 1.25
New BD14215FVJ-LA	2	2.7 to 5.5	310	-0.2 to +26	20	± 1 (Max)	-40 to +125	TSSOP-B8J 3.0x4.9, H=Max 1.10

照度传感器IC

电流输出型模拟照度传感器IC

Part No.	Supply Voltage (V)	Sensitivity Variations (%)	Detection Range (lx)	Sensitivity (μ A/lx)	IR Cut	I/F	Operating Temperature (°C)	Package
BH1603FVC	2.4 to 5.5	± 15	0 to 100,000	0.6	—	Linear Current Output (Source)	-40 to +85	WSOF6
BH1620FVC	2.4 to 5.5	± 15	0 to 100,000	0.6	—	Linear Current Output (Source)	-40 to +85	WSOF5
BH1680FVC	2.4 to 5.5	± 15	0 to 50,000	6	✓	Linear Current Output (Source)	-40 to +85	WSOF5
BH1682FVC	2.3 to 5.5	$\pm 3\mu$ A	1 to 55,000	—	✓	Logarithmic Current Output (Source)	-40 to +85	WSOF5

16bit串行输出型数字照度传感器IC

Part No.	Supply Voltage (V)	Sensitivity Variations (%)	Detection Range (lx)	Sensitivity (at 100ms) (lx/count)	IR Cut	I/F	Operating Temperature (°C)	Package
BH1721FVC	2.4 to 3.6	± 15	0 to 65,000	1	—	I ² C	-40 to +85	WSOF5
BH1730FVC	2.4 to 3.6	± 15	0 to 65,000	0.007	—	I ² C	-40 to +85	WSOF6
BU27034ANUC	1.7 to 2.0	± 15	0 to 20,000	0.000016	✓	I ² C	-40 to +85	WSON008X2120

颜色传感器IC

16bit串行输出型数字颜色传感器IC

Part No.	Supply Voltage (V)	λ_P (nm)				Illuminance Measurement (lx)	High Sensitivity	IR Cut	Fricker detection	I/F	Operating Temperature (°C)	Package (mm)
		Red	Green	Blue	IR							
BU27006MUC-Z	1.7 to 3.6	630	540	460	825	0 to 50,000	✓	✓	✓	I ² C	-40 to +85	WQFN12X2520A 2.5x2.0, H=Max 0.55

气压传感器IC

内置温度补偿功能数字气压传感器IC

Part No.	Supply Voltage (V)	Pressure Range (hPa)	Relative Pressure Accuracy (hPa)	Absolute Pressure Accuracy (hPa)	I/F	Operating Temperature (°C)	Waterproof	Package (mm)
BM1390GLV-Z	1.7 to 3.6	300 to 1,300	±0.06	±1	I ² C	-40 to +85	✓	RLGA10VG020T 2.0×2.0, H=Max 1.0

温度传感器IC

模拟输出温度传感器IC

Part No.	Supply Voltage (V)	Temperature Accuracy (°C)		Temperature Sensitivity (mV/°C)	Output Voltage (V) (T _s =+30°C, V _{DD} =3V)	Supply Current (μA)	Operating Temperature (°C)	Package
		T _s =+30°C	T _s =-30, +100°C					
BD1020HFV	2.4 to 5.5	±1.5	±2.5	-8.2	1.3	4.0	-30 to +100	HVSOF5

数字输出温度传感器IC

Part No.	Supply Voltage (V)	Temperature Accuracy (°C) T _s =-20 to +85°C	Current Consumption (μA)	I/F	Operating Temperature (°C)	Package
BH1900NUX	2.7 to 3.6	±3	75	I ² C	-30 to +95	VSON008X2030

震动传感器用放大器

震动传感器用放大器

Part No.	Supply Voltage (V)	Current Consumption (mA)	Notch Frequency (kHz)	Notch Attenuation Rate (dB)	Operating Temperature (°C)	Package
BD3852MUZ-Z	1.6 to 2.3	1.6 to 4.5	31.0	-23.0	-40 to +85	VQFN16Z3030A

加速度传感器

3轴加速度传感器

	Part No.	Acceleration Range (±g)	Mechanical Signal Bandwidth (Hz)	I/F	Operating Temperature (°C)	Size, No. of Pins, Package	Features
New	KX022ACR-Z	2, 4, 8, 16	800	I ² C/SPI	-40 to +85	2×2×1mm, 12pin, LGA	Wake-up and Back-to-sleep Function, 86sets (8bit) or 43sets (16bit) Buffer
New	KX132ACR-LBZ	2, 4, 8, 16	4,200 (XY) 2,900 (Z)	I ² C/SPI	-40 to +105	2×2×1mm, 12pin, LGA	Up to +105°C Operating Temperature, Up to 25.6kHz Output Data Rate, 86sets (8bit) or 43sets (16bit) Buffer
New	KX134ACR-LBZ	8, 16, 32, 64	8,200 (X) 8,500 (Y) 5,600 (Z)	I ² C/SPI	-40 to +105	2×2×1mm, 12pin, LGA	Up to +105°C Operating Temperature, Up to 25.6kHz Output Data Rate, Wide Mechanical Signal Bandwidth, 86sets (8bit) or 43sets (16bit) Buffer