

# CONDITION OF SOLDERING FOR SURFACE MOUNTED DEVICES (DISCRETE SIC) LEAD FREE PASTE (Sn-3Ag-0.5Cu) VERSION

Product	SiC SBD / SiC MOSFET	Package	Surface Mount Devices
1 TOGGOT	010 000 7 010 111001 21	i dollago	Carrace Meant Bevices

### 1. REFERENCE CONDITION FOR WASHING

#### 1-1.REFERENCE WASHING LIQUID


washing liquid		maker						
Water								
Ethanol								
Methanol								
Pine alpha	ST-100S	ARAKAWA CHEMICAL						
Clean through	750H	KAO						
Technocare	FRW-1	MOMENTIVE performance materials						
Mighty solve	AH-V	ASAHI GLASS						

### 1-2.REFERENCE CONDITION FOR WASHING

Washing bath		Time	Temperature	Remarks
F:	1111	00-	Room	05 00111- 45141/0
First bath	Ultrasonic bath	~60s	temperature	25~28kHz, 15W/cm3
			Room	
Second bath	Immersion bath	∼60s	temperature	
				Temperature is depending
Third bath	Vaper bath	~60s	~44.7°C	on washing liquid.

XIn vaper bath, you can not use ethanol, methanol, and water due to their high boiling points.

# 2.REFERENCE CONDITION FOR REFLOW SOLDERING



- ① Pre-heating rate 1~5°C/s
- ② Pre-heating • 130~170°C, 50~120 s
- ③ Heating rate · · 1~3°C/s
- ④ Soldering Over 217°C, 60~120 s
- ⑤ Peak temperature • •

245°C(TOLL:260°C)

**(6)** Cooling  $\cdot \cdot \cdot \cdot 1 \sim 6$  °C/s 245 $\sim 217$  °C

(TOLL:260~217°C)


7 Number of times 2 times max.

We concluded that there is no specific problem in characteristics and reliability under the temperature profile above.

However, since the most appropriate temperature profile condition differs depending on the solder paste, we highly recommend you to examine whether there is problem in your own condition.

CONDITION OF SOLDERING FOR SMD-SiC\_E

# 3.REFERENCE CONDITION FOR FLOW SOLDERING




# 4.REFERENCE CONDITION FOR HAND SOLDERING

Temperature · · · 350°C

Duration · · · · · less than 3 s

Number of times one time

# 5.REFLOW PROFILE FOR HEAT-RESISTANCE TEST



⊕Pre-heating · · · · · · · · 150~200°C, 60~120 s

②Heating rate······· 3°C/s max.

③Soldering · · · · · · · Over 217°C, 60~150 s


④Peak temperature ····· 245°C, Over 240°C 30 s

260°C, Over 255°C 30 s (TOLL)

©Cooling····· 6°C/s max 245~217°C

6°C/s max 260~217°C (TOLL)

CONDITION OF SOLDERING FOR SMD-SiC E



CONDITION OF SOLDERING FOR SMD-SiC\_E

### Notes

- 1) The information contained herein is subject to change without notice.
- Before you use our Products, please contact our sales representative and verify the latest specifications.
- 3) Although ROHM is continuously working to improve product reliability and quality, semiconductors can break down and malfunction due to various factors. Therefore, in order to prevent personal injury or fire arising from failure, please take safety measures such as complying with the derating characteristics, implementing redundant and fire prevention designs, and utilizing backups and fail-safe procedures. ROHM shall have no responsibility for any damages arising out of the use of our Poducts beyond the rating specified by ROHM.
- 4) Examples of application circuits, circuit constants and any other information contained herein are provided only to illustrate the standard usage and operations of the Products. The peripheral conditions must be taken into account when designing circuits for mass production.
- 5) The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. ROHM does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by ROHM or any other parties. ROHM shall have no responsibility whatsoever for any dispute arising out of the use of such technical information.
- 6) The Products are intended for use in general electronic equipment (i.e. AV/OA devices, communication, consumer systems, gaming/entertainment sets) as well as the applications indicated in this document.
- 7) The Products specified in this document are not designed to be radiation tolerant.
- 8) For use of our Products in applications requiring a high degree of reliability (as exemplified below), please contact and consult with a ROHM representative : transportation equipment (i.e. cars, ships, trains), primary communication equipment, traffic lights, fire/crime prevention, safety equipment, medical systems, servers, solar cells, and power transmission systems.
- Do not use our Products in applications requiring extremely high reliability, such as aerospace equipment, nuclear power control systems, and submarine repeaters.
- 10) ROHM shall have no responsibility for any damages or injury arising from non-compliance with the recommended usage conditions and specifications contained herein.
- 11) ROHM has used reasonable care to ensure the accuracy of the information contained in this document. However, ROHM does not warrants that such information is error-free, and ROHM shall have no responsibility for any damages arising from any inaccuracy or misprint of such information.
- 12) Please use the Products in accordance with any applicable environmental laws and regulations, such as the RoHS Directive. For more details, including RoHS compatibility, please contact a ROHM sales office. ROHM shall have no responsibility for any damages or losses resulting non-compliance with any applicable laws or regulations.
- 13) When providing our Products and technologies contained in this document to other countries, you must abide by the procedures and provisions stipulated in all applicable export laws and regulations, including without limitation the US Export Administration Regulations and the Foreign Exchange and Foreign Trade Act.
- 14) This document, in part or in whole, may not be reprinted or reproduced without prior consent of ROHM.



Thank you for your accessing to ROHM product informations. More detail product informations and catalogs are available, please contact us.

# ROHM Customer Support System

http://www.rohm.com/contact/

### **General Precaution**

- 1. Before you use our Products, you are requested to carefully read this document and fully understand its contents. ROHM shall not be in any way responsible or liable for failure, malfunction or accident arising from the use of any ROHM's Products against warning, caution or note contained in this document.
- 2. All information contained in this document is current as of the issuing date and subject to change without any prior notice. Before purchasing or using ROHM's Products, please confirm the latest information with a ROHM sales representative.
- 3. The information contained in this document is provided on an "as is" basis and ROHM does not warrant that all information contained in this document is accurate and/or error-free. ROHM shall not be in any way responsible or liable for any damages, expenses or losses incurred by you or third parties resulting from inaccuracy or errors of or concerning such information.

Notice – WE Rev.001